



# CLP-7210e & CLP-7401 BARCODE LABEL PRINTER

<b>SPECIFICATION</b>	<b>7210e</b>	<b>7401</b>
Print Technology	Direct Thermal/Thermal Transfer	Direct Thermal/Thermal Transfer
Print Speed	2-7ips	1-4ips
Print Resolution	200DPI	400DPI
Print width	1"to 4.09"(25mm to104mm)	1"to 4.09"(25mm to104mm)
Print Length	0.25" to 32"	0.25" to 10"
Construction	Steel chasis,Steel cabinet	Steel chasis,Steel cabinet
Label thickness	0.0025" to 0.0067"(0.06mm to 0.25mm)	0.0025" to 0.0067"(0.06mm to 0.25mm)
Label width	4.65"Maximum(118mm) 1" Minimum(25mm)	4.65"Maximum(118mm) 1" Minimum(25mm)
Roll outside diameter	Up to 8" OD Standard	Up to 8" OD Standard
Roll core diameter	1" to 3" ID(25mm to 76mm)	1" to 3" ID(25mm to 76mm)
Ribbon length	1,311 ft.(400m)	1,311 ft.(400m)
Ribbon width	up to 4.25"(108mm)	up to 4.25"(108mm)
Memory	2 MB DRAM,1MB Flash ROM standard; 4 MB additional Flash	2 MB DRAM,1MB Flash ROM standard; 4 MB additional Flash
Dimension	9.9"H x 10"W x16.9"D (251mmH x 254mmW x 428mmD)	9.9"H x 10"W x16.9"D (251mmH x 254mmW x 428mmD)
Weigth	24.2 lbs.(11.0kg)	24.2 lbs.(11.0kg)

## Common Feature

Barcodes supported	Bookland;Codabar;Code 39,mod43; Code 93;Code 128 A, B, C, Auto-switch,F1 Mod 10;EAN-8, Plus 2,Plus 5; EAN-13, Plus 2,Plus 5; EAN-128; HIBCC;IAN;ISSN; Interleaved 2 of 5,14,16,mod 10; ISBN;ISDN;JAN;NW-17;Plessey;Postnet; Telepen; UCC 128;UCC/EAN-128,Multi;UPC-A,Plus-2,Plus 5;UPC-E,Plus2,Plus 5,Shipping Container; 2-Dimensional:Maxicode,PDF-417,QR Code
Resident Fonts	TrueType scaleable fonts can be downloaded. Resident fonts include:CG Triumvirate Regular and Bold sizes3-6,8,10,12, 14,18,24,30,36,48 point;OCR-A,OCR B;9 alphanumeric System Fonts
Display	LCD panel with Pause,Feed,and Stop functions;LED status.mode, and error information
Communications	RS232C Serial and Centronics Parallel Standard; Ethernet and Wireless connectivity optional
Software	Compatible with Label View Software for Windows
Enviromental Conditions	Operating Temperature;5 degree celsius to 49 degress celsius;Humidity;30% to 85%,non-condensing
Power requirement	120V or 240V
Agency Appovals	UL,CSA,FCC,EN55022,EN55024,EN50082,EN60950,EN61000
Optional & Accessories	Label View Software for window,1 MB Flash PCMCIA Memory Card,External Card,Label/Rewinder

ALTECH INDUSTRIES

3016 Bedok North Ave 4 EASTech #06-06

Singapore 484497

Phone:65-2460515

Fax:65-2461992

<http://www.altech1.com>

All trademarks are the property of their respective owner.Specification are subject to change at any time